

Image-8

Product Overview

Custom Conveniences For The Custom Installing Pro

The Image 2-Way in-wall speaker systems deliver unmatched performance, their ability to reproduce the full ranges of music with no strain or distortion earn it high marks in multitasking. Their smooth reproduction of music with no overhang is the product of an elaborate signal processing network; so precise, it allows for seamless sound transition. The Image speaker system is designed to channel the impact of special effects onto viewers; in crystal-clear, subtle fashion that makes listeners become part of the scene.

The Image speakers gently lend themselves to the interior of any home, they bring the excitement and the drama of crisp clean music to your kitchen, bedroom, and every other room. Great for rear channel surround sound application, or for a remote location; the Earthquake Image drivers are equipped with TURN 'N' LOCK™ mechanism for easy installation.

Very High Sensitivity And Power Handling another way that Earthquake delivers value and performance in one low cost package

Paintable Rust-proof Aluminum Grilles for superior protection and job flexibility

Turn -N- Lock Installation for safe, efficient and professional installs

PistonMax Woofer Design for more accurate mid-bass with out distortion

Poly Injection Composite Drivers for smooth widerange response with low distortion

Five Models to choose from: Image-5, Image-6, Image-8, Image-C25 and IW-846X

Long Life, Moisture Resistant Materials including butyl rubber surrounds and poly injection cones for safe use in kitchens, bathrooms and atriums

Image Style easily integrates with Image in-wall speakers and even Earthquake IQ speakers



SPECIFICATIONS

| | |
|----------------------------|--|
| Frequency Response: | 52Hz - 21kHz |
| Sensitivity: | 90dB @ 1W/1M |
| Nominal Impedance: | 8-Ohm |
| Power Handling: | 50 - 200 Watts |
| Enclosure Material / Type: | Infinite baffle, flush with wall |
| Drive Components: | Two-way system using: One 3/4" silk dome compression tweeter and one 8" expanded surround poly-mica cone woofer |
| Wire Gauge Recommended: | 12 |
| Weight: | 12.40lbs. |
| Grille Frame Diameter: | 14 1/8" x 10 1/16" • 359mm x 256mm |
| Cut Out Hole Diameter: | 12 7/8" x 8 5/8" • 324mm x 221mm |
| Mounting Depth: | 3 7/8" • 98mm |
| Finish: | White / Paintable |

